MODEL VARIATION

1-J3.5 Ton Models











MAIN SPECIFICATIONS

Model		8FG10 8FD10	8FG15 8FD15	8FG18* 8FD18*	8FGK20* 8FDK20*	8FG20 8FD20	8FGK25* 8FDK25*	8FG25 8FD25	8FGK30* 8FDK30*	8FG30 8FD30	8FGJ35 8FDJ35
Engine Model	Gasoline	4Y	4Y	4Y	4Y	4Y	4Y	4Y	4Y	4Y	4Y
Liigiile Wouel	Diesel	1DZ-Ⅱ	1DZ-II	1DZ-II	1DZ-Ⅱ	1DZ- I ,2Z	1DZ-Ⅱ	1DZ-I ,2Z	1DZ-Ⅱ	1DZ-Ⅱ,2Z	1DZ-II ,2Z
Load Capacity	kg	1,000	1,500	1,750	2,000	2,000	2,500	2,500	3,000	3,000	3,500
Load Center	mm	500	500	500	500	500	500	500	500	500	500
Overall Width A	mm	1,045	1,070	1,070	1,155	1,150	1,155	1,150	1,255	1,240	1,290
Turning Radius (outside) B	mm	1,910	1,990	2,010	2,040	2,200	2,090	2,280	2,130	2,430	2,490
Overhead Guard Height C	mm	2,080	2,080	2,080	2,085	2,110	2,085	2,110	2,085	2,170	2,180
Length to Fork Face D	mm	2,240	2,285	2,310	2,360	2,550	2,420	2,620	2,505	2,775	2,845

NOTE: *Powershift models

Model	8FG35N 8FD35N	8FG40N 8FD40N	8FG45N 8FD45N	8FG50N 8FD50N	8FD60N	8FD70N	8FD80N	
Engine Model	Gasoline	1FS	1FS	1FS	1FS	-	-	_
Liigille Wodel	Diesel	14Z- I I	14Z- I I	14Z-Ⅱ	14Z- I I	14Z-Ⅱ	14Z- I I	14Z-Ⅱ
Load Capacity	kg	3,500	4,000	4,500	5,000	6,000	7,000	8,000
Load Center	mm	600	600	600	600	600	600	600
Overall Width A	mm	1,350	1,350	1,450	1,450	1,965	1,965	1,965
Turning Radius (outside) B	mm	2,610	2,660	2,750	2,810	3,230	3,280	3,320
Overhead Guard Height C	mm	2,210	2,210	2,300	2,300	2,310	2,310	2,310
Length to Fork Face D	mm	2,925	2,980	3,110	3,170	3,490	3,545	3,590





The data in this brochure is determined based on our standard testing condition.

The performance may vary depending on the actual specification and condition of the vehicle as well as the condition of the operating area. Availability and specifications depend on region and are subject to change without notice.

Due to photography and printing, color of actual vehicle may vary from this brochure. Some photos have been computer-enhanced. Please consult your Toyota representative for details.

All rights reserved by Toyota Industries Corporation.






TOYOTA MATERIAL HANDLING INTERNATIONAL +62 8136 9614 067

sales@win-equipment.co.id www.win-equipment.co.id















The 8 Series deploys a high-reliability Toyota engine, with the power and durability to support all your operations.

5A5 70

Uncompromising and ample functioning is also delivered by Toyota engines.

Line-up of Reliable Toyota Engines



Low Fuel Consumption

With new engine(gasoline models) and Load-sensing power steering, 8FG/D35-80 achieves low fuel consumption.









NEW Load-sensing Power Steering (LSPS)

3.5 - 8 ton models

This adjusts the amount of power-steering fluid according to the load burden on the rear axle, reducing energy loss and helping to enhance fuel economy.

NEW 2-stator Torque-converter and Transmission

3.5 - 8 ton models

A 2-stator torque-converter is used to achieved optimal drive power and travel speed with no gear-change. The high-efficiency torque-converter and transmission help to reduce fuel consumption.

NEW Eco-mode OPT

3.5 - 5 ton gasoline models

This restricts acceleration for traveling and load handling, further helping to improve fuel efficiency.

Note: This is included in Multifunction Display (OPT) and Deluxe Multifunction Display (OPT).

NEW Engine Auto Stop OPT

This feature automatically stops the engine if the operator sets the parking brake but forgets to turn off the engine and leaves seat longer than a preset time. This contributes to lower fuel consumption. Note: This is included in Deluxe Multifunction Display (OPT).

Make sure to follow proper parking process when parking the forklift. (e.g. turn off the engine)

Diesel Particulate Filter DPF-II OPT

This uses an enhanced filtering system to provide excellent black smoke particle elimination.









Toyota's original safety technology to boost work efficiency

The 8 Series incorporates Toyota's own innovative safety equipment, including SAS and OPS.

These features provide stable and smooth operation, and can even help boost work efficiency.

System of Active Stability SAS OPT

Active Control Rear Stabilizer






An onboard computer monitors the movement of the forklift and locks the swing of the rear axle when necessary, such as during turns.


Note: This function is not installed when the forklift is equipped with dual front tires.

Active Steering Synchronizer

With Active Steering Synchronizer







This feature ensures that the angle of the steering wheel corresponds to the angle of the rear steered wheels.

Active Mast Function Controller



Active Mast Front-tilt Angle Control

The angle of the forward mast tilt is automatically controlled to match the lift height and load weight, helping to prevent dropped loads or tip-overs.



Active Mast Tilt Speed Control

Automatic control of the mast tilt speed at high mast heights, helps to prevent load spills.



Automatic Fork-leveling Control

Pressing a switch during forward tilt automatically stops the forks at a level position. This makes load-handling operations easier, helping to achieve high productivity.

Operator Presence Sensing System **OPS**



This system uses a switch sensor built into the operator's seat to detect the presence of the operator. If the operator is not in the normal operating position, travel power is interrupted and load handling operations are stopped.

Features and equipment may vary depending on market.

Note: OPS does not operate the brakes. Make sure to follow proper process when you leave the forklift. (e.g. set the parking brake) Travel OPS is not available on manua

Key-lift InterLock

This locks fork-lifting down operation when the key switch is off, preventing fork descent in the event of inadvertent lever operation.

Travel and Load-handling Control

Maximum Speed Limitation

1 - J3.5 ton models OPT* 3.5 - 5 ton gasoline models OPT*

This feature enables to limit the maximum speed to a preset level. This helps operators maintain certain speed limits in the work area.

Low-speed Setting

1 - J3.5 ton models OPT* 3.5 - 5 ton gasoline models OPT*

This feature limits the maximum speed to a preset level when the switch is pressed. This can be useful at locations such as customer worksites that have different speed rules for outdoor and indoor operations.

Lift-height and Load-sensing Vehicle Speed Control

1 - J3.5 ton models / Powershift models OPT*

This feature limits the maximum speed depending on lift-height and load weight, thereby helping to reduce the likelihood of instability.

Lift-height and Load-sensing Sudden Start Off Prevention Feature

1 - J3.5 ton models / Powershift models OPT*

This feature suppresses sudden acceleration of the vehicle to help to reduce the risk of load spills when starting to the forklift after loading at high lift height.

Automatic Idle-up Device

1 - J3.5 ton models OPT*

The idle revolution of the engine is automatically increased during lifting operations so that loads will be smoothly lifted without depressing the accelerator.

*Selection of these features requires installation of additional options as well. For details, please see the option chart on page 13.

Note: The vehicle may not reach or may exceed set speed. This feature does not eliminate the possibility of tip-over, but helps reduce the potential of forklift instability.





For Reverse-Travel Operation

Outstanding visibility for high performance

The 8 Series, designed from a workplace perspective, provides a clear view of the fork tips and areas around the forklift. This outstanding visibility supports safe and accurate operation.








For Entry & Exit

The seat swivels 17.5 degrees to the right, enabling the operator to maintain a comfortable posture when reversing. The seat also swivels 20 degrees to the left,



Rear-pillar Assist Grip OPT

This assist grip with horn button supports the driving position and offers easy horn operation while traveling in reverse







ENGINE POWERED FORKLIFT

Designed for outstanding operability and operator comfort

You find an outstanding comfort as soon as you get on the 8 Series. A compact but roomy body, a small-diameter steering wheel, and other operator-friendly design features of the 8 Series provide you with comfortable and efficient operation.

Easy Entry and Exit





Wide Floor Space

The spacious floor space enables a more relaxed operating position that contributes



The ORS seat can be adjusted 150 mm and supports a comfortable operating posture by means of side wings and a seatbelt. *ORS: Operator Restraint System





Foot-activated Parking Brake

Small-diameter Steering Wheel

The small-diameter steering wheel teams up with the full hydraulic power steering system to provide excellent maneuverability. The steering column offers stepless adjustment to accommodate a wide



Parking Brake

The 8 Series uses a double-action parking brake that has a release button to prevent inadvertent disengagement.

The 8FG/D10 to J35 Powershift models use a foot-operated parking brake that can be engaged with just a single foot-press.

Easy-down System

When the forks are lowered, this system controls the speed of descent before the forks touch with the ground, contributing to reducing the noise of impact.



These small, easy-to-operate levers provide total load handling operation and travel direction selection. A fatigue-reducing armrest is provided.





Joystick OPT

Both lift and tilt operations are controlled by a single lever. Simultaneous lifting and tilting can be operated.

Cabin with Folding Door 1-J3.5 ton models OPT Steel Cabin 3.5-8 ton models OPT

This helps ensure comfort by shielding the operator against low temperatures, wind, and precipitation in cold climates







Features for high durability and reliability

High water resistance, self-protective features such as an engine-protection function, and other features of the 8 Series boost reliability and durability. What's more, the 8 Series is equipped with many ease-of-service features. These all help extend vehicle life.

Multifunction Display OPT Deluxe Multifunction Display OPT

The Multifunctional Display offers useful information for operations. The following are some of the display screens.











Combination Meter **Engine-protection Function**

Necessary instrumentation, such as the fuel meter, water temperature indicator and hour meter are shown in an easy-to-monitor digital format.



When the engine controller detects a malfunction such as high engine water temperature, this function automatically restricts engine output or stops the engine and informs the operator by the combination meters, to help prevent further

Torque-converter Interlock OPT

When the operator attempts switchback during high-speed travel, this automatically shifts the vehicle into neutral. After vehicle speed is reduced to below a preset level, the vehicle changes its driving direction.

This reduces excessive strain on the torque converter, and also reduces tire wear due



Radiator Cover

No tools are needed to remove the easily be turned by hand to enable quick it and the oil seals. inspections or servicing.



Tilt Cylinder Boots

Each boot covers the exposed portion radiator cover. The fastening knobs can of the rod for the tilt cylinder, protecting



Water-resistant Connectors

Connectors for most electrical components are highly water-resistant, increasing the reliability of the electrical system



LED Headlights OPT

the headlights and rear working lights.

LED Rear Working Lights OPT

Power-saving, long-life LED lights are available for

Hood Latch The easy-to-operate latch provides quick access to the engine compartment.

Floorboard of Two-piece Design

The rear boards can be removed without using tools, providing easy access during daily operator checks.





STANDARD EQUIPMENT

- Wide Visible Mast Load backrest (V and FSV masts) Easy-down system (8FG/D10.j35 V mast) Alternator with IC regulator Intake heater (2Z,14Z-II engine models) Super glow control system (1DZ-II engine models)
- Sedimenter (Diesel models) Same key for multiple forklifts 2-stator T/C (8FG/D35-80) Tilt cylinder boots Radiator screen(8FG/D35-80) Cyclone air cleaner with snorkel air intake
- Engine protection system (8FG35-50 Gasoline models) Electronic fuel injection system (8FG35-50 Gasoline models) Radiator reservoir tank Operator Presence Sensing System (OPS)
- Double-action parking brake [8FG/D10J35 Powershift models,8FG/D35-80] / Foot-activated parking brake [8FG/D10J35 Manual transmission models] Assist grip Neutral safety switch
- Electrical shift control (Powershift models) Full hydraulic power steering Tilt steering column Overhead guard sheet Overhead guard Hidden tilt cylinder Engine hood damper (Lockable) Jack point
- Drawbar pin Engine hood insulation Headlights Headlights guard Rear combination lights (8FG/D35-80) Integrated light & turn signal switch Hour meter Engine water temperature indicator Fuel meter
- Engine oil pressure warning light Charge warning lights Pre-heat indicator light (Diesel engine models) Sedimenter warning light (Diesel engine models) Electric horn Cup holder ORS seat

MAIN OPTIONS

●:OPT ○:STD

		8FG/8FI	110. ISE	8FG/8FD	3EM-EUN	8FD60N-80N	O:OPT O:ST
	ITEM	Gasoline	Diesel	Gasoline	Diesel	Diesel	(Option must be chosen with)
	Eco-mode (Deluxe Multifunction Display or Multifunction Display)	udsonne -	- Diesei	dasonne	- Diesei	DI6261	(Option must be chosen with)
	Engine Auto Stop (Deluxe Multifunction Display)		-		-	-	
	0 1 7	•	•		•	•	
	Catalytic Muffler		•	•	_	-	SAS(8FG10-J35)
Environment	3-way Catalytic Converter System		•	_	•	•	SAS(8FG10-J35)
	Diesel Particulate Filter DPF-II						
	LPG Fuel System	•	-	•	-	-	
	Spark Guard Net	•	•		•	•	
	Upswept Exhaust	•	•	•	•	•	
	System of Active Stability (SAS)	•	•	•	•	•	
	Fan Guard	-	-	•	•	•	
	Yellow Beacon On Overhead Guard	=	-	•	•	•	
	Yellow Strobe Light On Overhead Guard	•	•	•	•	•	
	Front Combination Lights	•	•	•	•	•	
	Rear Combination Lights	•	•	0	0	0	
Safety &	Back-up Buzzer	•	•	•	•	•	
Stability	Rear-view Mirrors (Right and left sides)	•	•	•	•	•	
,	Travel and Load-handling Control						8FG/D10-J35:
	Maximum Speed Limitation	•	•	•	-	-	SAS, Catalytic Muffler (Gasoline models
	Low-speed Setting	•	•	•	-	-	Deluxe Multifunction Display
	Lift-height and Load-sensing Vehicle Speed Control		•	-	-	-	8FG35-50:
	Lift-height and Load-sensing Sudden Start Off Prevention Feature	•	•	-	_	-	SAS (For Maximum Speed Limitation)
	Automatic Idle-up Device			-	 	 	(Deluxe) Multifunction Display (For Low-speed Setting)
				•	•	•	, com opena colling)
	Rear-pillar Assist Grip						
	Swivel Seat	•	•	•	•	•	1
	Suspension Seat w/ Damper	•	•	•	•	•	
	Mini Lever	•	•	•	•	•	SAS, (Deluxe) Multifunction Display, 3-Way Catalytic Converter System
	Joystick	•	•	•	•	•	3-Way Catalytic Converter System (8FG/D10-J35)
	Steel Cabin	<u> </u>	-	•	•	•	
	Cabin w/ Folding Door	•	•	-	-	-	
	Deluxe Cabin	(Only 2-J35t)	(Only 2-J35t)	-	-	-	
	Front Windshield w/ Wiper and Washer	•	•	•	•	•	
Operability &	Canvas Cabin w/ Wiper and Washer	•	•	_	-	_	
	Heater	•	•	•	•	•	
Comfort	Defroster		•		•	•	Heater, Cabin option
	Floor Mat		•		•	•	пеаці, самі орион
	Mast Tilt Indication		•		•	•	
	Document Box			•	•	•	
	Fork Noise Reducer	•	•	-	-	-	
	Fork Vibration Damper	•	•	-	-	-	
	Oil Clutch (Manual Transmission)	•	•	-	-	-	
	2-stator Torque-converter	●(Only 2-J35t)	(Only 2-J35t)	0	0	0	
	LSD (Limited-Slip Differential)	●(Only 2, 2.5t)	(Only 2, 2.5t)	-	-	-	
	Torque-converter Interlock	-	-	•	•	•	SAS, (Deluxe) Multifunction Display
	Fully Oil Charged Lift Cylinder	•	•	•	•	•	
	Tilt Cylinder Hole Boots	•	•	•	•	•	
	Power Steering Cylinder Boots	_	-	•	•	•	
Durability	Long Life Coolant 50%	•	•	•	•	•	
	LED Head Lights / LED Rear Working Light	_*	_*	•	•		
	Head Lights Guard (for Front Combination Lights)	_	_	•	•	•	Front Combination Lights
		•	•				Horit Combination Lights
	Anti-restart Ignition Key Switch	•					242
	Multifunction Display						SAS
	Deluxe Multifunction Display	•	•	•	•	•	SAS, Anti-restart Ignition Key Switch (1FS engine
Service &	OK Monitor	•	•	•	•	•	SAS(8FG/D10-J35)
Management	Key off Head Lights off System	-	-	•	•	•	
	Key-less Ignition Switch	•	•	-	-	-	
	Fuel Tank Cap with Key	•	•	•	•	•	
Special Edition	High-capacity Cooling Spec	•	•	•	•	•	Oil Clutch (8FG/D10-J35)
	Cooling Fan Booster Kit	-	-	•	•	•	
	Cold Area Package	-	●(Only 2Z)	-	•	•	
	Low-noise Model	•	•	•	•	•	
	Rust-proof Model	•	•		-	-	1
	Cyclone Air Cleaner (Dual Elements)	•	•	•	•	•	
			•			•	1
	Pre-Cleaner						-
	Plate Fin Type Radiator	-	-	•	•	0	1
	Radiator Screen	•	•	0	0	0	.
	Heavy Duty Mast	-	-	●(Only 3.5, 4t)	●(Only 3.5, 4t)	-	1
	High-capacity Alternator	•	•	•	•	•	
	High-capacity Alternator High-capacity Battery	•	•	•	•	•	

*Bulb Rear Working Light is available

